According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Trade name	:	MOLYKOTE(R) W 15	
Company	:	Dow Corning S.A. rue Jules Bordet - Parc Industriel - 2 B-7180 Seneffe Belgium	Zone C
Service	:	Dow Corning Central Europe	Tel: +49 6112371 Fax: +49 611237609
		Dow Corning Northern Europe	Tel: +44 1676528000 Fax: +44 1676528001
		Dow Corning Southern Europe	Tel: +33 472841360 Fax: +33 472841379
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h)	Tel: +44 1446732350
		Dow Corning (Wiesbaden 24h)	Tel: +49 61122158
		Dow Corning (Seneffe 24h)	Tel: +32 64 888240
Use of the substance/preparation	:	Lubricants and additives	

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Mixture of inorganic and organic compounds

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4	265-090-8	33.0		
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	33.0		
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	23.0		
Calcium dihydroxide	1305-62-0	215-137-3	14.0	Xi	R38 R41
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based	72623-87-1	276-738-4	11.0		
Hydrotreated Neutral Oil, C15-C30	72623-86-0	276-737-9	2.3		

DOW CORNING

PRODUCT SAFETY DATA SHEET

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments. This information is based on test data from similar products.

4. FIRST AID MEASURES On contact with eyes : Flush with water. On skin contact : Flush with water. If inhaled : Remove to fresh air. On ingestion : No first aid should be needed.

5. FIRE FIGHTING MEASURI	ES	
Suitable extinguishing media	:	Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
Unsuitable extinguishing media	:	None known.
Hazards during fire fighting	:	None known.
Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
Hazardous Combustion Products	:	Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	:	Wear proper protective equipment.			
Precautions to protect the environment	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.			
Methods for cleaning up	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.			

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

7. HANDLING AND STORAGE Advice on safe handling : General ventilation is recommended. Local ventilation is recommended. Avoid skin and eve contact.

		eye contact.
Advice on storage	:	Do not store with oxidizing agents.
Specific uses	:	Refer to technical data sheet available on request.
Unsuitable packaging materials	:	None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering	Controls

: Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name	CAS-No.	Exposure Limits
Distillates (petroleum), solvent refined heavy paraffinic	64741-88-4	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Calcium dihydroxide	1305-62-0	5 mg/m3 TWA
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil based	72623-87-1	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Hydrotreated Neutral Oil, C15-C30	72623-86-0	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Personal protection equipment	<u>t</u>	
Respiratory protection	confined space exceeded. A suitable resp aerosol or mist A full-face mas Recommended The choice of a	atory protection should be worn if the product is used in large quantities, s or in other circumstances where the OEL may be approached or irator must be worn if the product is used in any circumstances where an may be generated, such as during spraying or similar activities. sk is recommended. Filter type: ABP a filter type depends on the amount and type of chemical being handled in Regarding filter characteristics, contact your respiratory protection

DOW CORNING

PRODUCT SAFETY DATA SHEET

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

	MOLYKOTE(R) W 15	
Hand protection	: Chemical protective gloves should be worn where repeated or prolonged contact ca occur: 4H(TM). Viton(TM). Silver shield(TM). Polyvinyl alcohol(PVA). Regard glove's breakthrough time,contact your chemical protective glove supplier.	
Eye protection	: Safety goggles should be worn.	
Skin protection	: Protective equipment is not normally necessary.	
Hygiene measures	: Exercise good industrial hygiene practice. Wash after handling, especially before ea drinking or smoking.	ating,
Environmental exposure controls	: Refer to section 6 and 12.	
Additional information	: These precautions are for room temperature handling. Use at elevated temperature of aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC. or contact the Dow Corning customer service group.	e refer r

<u>Appeara</u>	ince					
Form:	Liquid		Colour:	Straw	Odour:	None
<u>Importa</u>	nt health, safety a	and envi	ronmental inf	formation		
Boiling p	point/range	:	>= 65 °C			
Flash po	int	:	> 200 °C (Pe	ensky-Martens C	Closed Cup)	
Explosiv	e properties	:	No			
Specific	Gravity	:	0.94			
Viscosity	7	:	140 cSt at 25	ö°C.		
Oxidizin	g properties	:	No			

10. STABILITY AND REACTIVITY				
Stability	:	Stable under normal usage conditions.		
Conditions to avoid	:	None established.		
Materials to avoid	:	Can react with strong oxidising agents.		

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

Hazardous decomposition	:	If this product is heated to > 150 degrees C, trace quantities of formaldehyde may be
products		released, and adequate ventilation is required. See section 11.

11. TOXICOLOGICAL INF	ORMA	TION
On contact with eyes ²	:	Slightly irritating.
On skin contact ²	:	Slightly irritating.
If inhaled	:	No adverse effects are normally expected.
On ingestion	:	Small amounts transferred to the mouth by fingers during use should not injure. Swallowing large amounts may cause digestive discomfort.
Other Health Hazard Information	:	Product may emit formaldehyde vapour at temperatures above 150°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected. This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

The product is poorly biodegradable.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No specific information is available.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDE	TIONS
Product disposal	: Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
Packaging disposal	: Dispose of in accordance with local regulations. Waste codes should be assigned by th user, preferably in discussion with the waste disposal authorities.

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

Labelling according to EEC Directive

S-phrases

S24/25 Avoid contact with skin and eyes. S51 Use only in well-ventilated areas.

This information is based on test data from similar products.

:

National legislation / regulations

Ozone depleting
chemicals:No ozone depleting chemicals are present or used in manufacture.Status::EINECS:All ingredients listed or exempt.TSCA:All chemical substances in this material are included on or exempted from listing on the
TSCA Inventory of Chemical Substances.

DOW CORNING

PRODUCT SAFETY DATA SHEET

According to EC directive 91/155/EEC and subsequent amendments

Version: 1.6 Revision Date: 18.07.2006

MOLYKOTE(R) W 15

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R38 Irritating to skin., R41 Risk of serious damage to eyes., R65 Harmful: May cause lung damage if swallowed.