

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Trade name : MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

Company : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Belgium

Service : Dow Corning (Wiesbaden) Tel: +49 611237507

Fax: +49 611237601

Dow Corning (Seneffe) Tel: +32 64511156

Fax: +32 64888683

Emergency Phone Number : Dow Corning (Barry U.K. 24h)

Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240

Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)

E-mail address (Safety Data

Sheet)

sdseu@dowcorning.com

Use of the : Lubricants and additives

substance/preparation

2. HAZARDS IDENTIFICATION

The principal hazards of the product as supplied are:

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Organic grease

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification
White mineral oil (petroleum)	8042-47-5	232-455-8	78.0	

Zinc oxide 1314-13-2 215-222-5 5.0 N R50/53 Benzenepropanoic Acid, 41484-35-9 255-392-8 0.25 N R51/53

3,5-Bis(1,1-Dimethylethyl)-4-

Hydroxy-,

Thiodi-2,1-ethanediyl Ester

4. FIRST AID MEASURES

On contact with eyes : No first aid should be needed.

1 of 7



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

On skin contact : No first aid should be needed.

If inhaled : Remove to fresh air.

On ingestion : No first aid should be needed.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon

dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed

containers.

Unsuitable extinguishing

media

None known.

Hazards during fire fighting : None known.

Special protective

equipment/procedures

A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

Hazardous Combustion

Products

Thermal breakdown of this product during fire or very high heat conditions may evolve

the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear proper protective equipment.

Environmental precautions: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or

other appropriate barriers.

Methods for cleaning up : Scrape up and place in a container fitted with a lid. The spilled product produces an

extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling : General ventilation is recommended. Local ventilation is recommended. Avoid eye

contact. Do not breathe spray or mist. Do not breathe fumes.

Advice on storage : Do not store with oxidizing agents.

Specific uses : Refer to technical data sheet available on request.

Unsuitable packaging

materials

None known.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name CAS-No. Exposure Limits

White mineral oil (petroleum) 8042-47-5 10 mg/m3 STEL Oil Mist,mineral

5 mg/m3 TWA Oil Mist,mineral

Personal protection equipment

Respiratory protection: Suitable respiratory protection should be worn if the product is used in large quantities,

confined spaces or in other circumstances where the OEL may be approached or

exceeded.

A suitable respirator must be worn if the product is used in any circumstances where an

aerosol or mist may be generated, such as during spraying or similar activities.

Depending on the working conditions, wear a respiratory mask with filter(s) BP or use a

self-contained respirator.

The choice of a filter type depends on the amount and type of chemical being handled in

the workplace. Regarding filter characteristics, contact your respiratory protection

supplier.

Hand protection : Gloves are not normally required.

Eye protection : Safety glasses should be worn.

Skin protection : Protective equipment is not normally necessary.

Hygiene measures : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

Environmental exposure

controls

Refer to section 6 and 12.

Additional information: These precautions are for room temperature handling. Use at elevated temperature or

aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form: Grease Colour: White Odour: Slight

Important health, safety and environmental information

Flash point : 215 °C (Closed Cup)

Explosive properties : No



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

Specific Gravity : 0.89

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Stability : Stable under normal usage conditions.

Conditions to avoid : None established.

Materials to avoid : Can react with strong oxidising agents.

Hazardous decomposition

products

Thermal breakdown of this product during fire or very high heat conditions may evolve

the following decomposition products: Carbon oxides and traces of incompletely burned

carbon compounds. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

On contact with eyes : May cause temporary discomfort.

On skin contact : No adverse effects are normally expected.

If inhaled : No adverse effects are normally expected.

On ingestion : No adverse effects are normally expected.

Other Health Hazard

Information

This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the

current physical form of the product, which is not in a respirable form.

Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

Environmental fate and distribution

Solid material, insoluble in water.

Ecotoxicity effects

Toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. However, due to the physical form and water-insolubility of the product the bioavailability is negligible.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

13. DISPOSAL CONSIDERATIONS

Product disposal : This material must be disposed of as hazardous waste. According to the European Waste

Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal

authorities.

Packaging disposal : Dispose of in accordance with local regulations. Waste codes should be assigned by the

user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

UN No. : UN 3077

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(Zinc Oxide)

Class : 9

Packing group : III

Labels : 9

Sea transport (IMDG)

UN No. : UN 3077

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.(Zinc Oxide)

Class : 9

Packing group : III

Emergency Schedule

: F-A S-F

Marine pollutant

(EmS)

Zinc Oxide

•

Labels : miscellaneous

Air transport (IATA)

UN No. : UN 3077

Proper Shipping Name : Environmentally hazardous substance, solid, n.o.s.(Zinc Oxide)

Class : 9

Packing group : III

Labels : Miscellaneous dangerous goods



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

: Apply Gross Wt Supplemental Label to Outer Package if shipping Limited Quantity

15. REGULATORY INFORMATION

Labelling according to EEC Directive

Symbols : N Dangerous for the environment.

R-phrases: R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

S-phrases : S29 Do not empty into drains.

S51 Use only in well-ventilated areas.

S57 Use appropriate container to avoid environmental contamination. S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

National legislation / regulations

Ozone depleting

chemicals

No ozone depleting chemicals are present or used in manufacture.

Status

DSL : Consult your local Dow Corning office.

EINECS : All ingredients listed, exempt or notified (ELINCS).

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

IECSC : All ingredients listed or exempt.

KECL : One or more ingredients are not listed or exempt or identified.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0

Revision Date: 04.12.2009

MOLYKOTE(R) G-0050 FG WHITE EP BEARING GREASE

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment., **R51/53** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.