

## MOLYKOTE(R) L-1568 PROCESS GAS OIL

## 1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Trade name	:	MOLYKOTE(R) L-1568 PROCESS GAS OIL
Company	:	Dow Corning S.A. Parc Industriel - Zone C B-7180 Seneffe Belgium
Service	:	Dow Corning Central Europe Dow Corning Northern Europe Dow Corning Southern Europe
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)
		Tel: +49 6112371 Fax: +49 611237609 Tel: +44 1676528000 Fax: +44 1676528001 Tel: +33 472841360 Fax: +33 472841379 Tel: +44 1446732350 Tel: +49 61122158 Tel: +32 64 888240

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

**Chemical characterization:** Inorganic and organic compounds in synthetic oil

**Hazardous Ingredients:**

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	Exempt or not available	98.0	

## 3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

## 4. FIRST AID MEASURES

On contact with eyes	:	No first aid should be needed.
On skin contact	:	No first aid should be needed.
If inhaled	:	No first aid should be needed.
On ingestion	:	No first aid should be needed.

## 5. FIRE FIGHTING MEASURES

## MOLYKOTE(R) L-1568 PROCESS GAS OIL

<b>Suitable extinguishing media</b>	:	Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
<b>Unsuitable extinguishing media</b>	:	None known.
<b>Hazards during fire fighting</b>	:	None known.
<b>Special protective equipment/procedures</b>	:	A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
<b>Hazardous Combustion Products</b>	:	Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	:	Wear proper protective equipment.
<b>Precautions to protect the environment</b>	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers. Do not empty into drains.
<b>Methods for cleaning up</b>	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

## 7. HANDLING AND STORAGE

<b>Advice on safe handling</b>	:	Avoid eye contact. General ventilation is recommended. Local ventilation is recommended. Do not breathe spray or mist.
<b>Advice on storage</b>	:	Do not store with oxidizing agents.
<b>Specific uses</b>	:	Refer to technical data sheet available on request.
<b>Unsuitable packaging materials</b>	:	None known.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls** : Ventilation : Refer to Section 7

**Exposure controls for hazardous components**

Name	CAS-No.	Exposure Limits
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	5 mg/m3 TWA, 10 mg/m3 STEL as paraffin oils (ACGIH).

**MOLYKOTE(R) L-1568 PROCESS GAS OIL****Personal protection equipment**

- Respiratory protection** : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.
- Hand protection** : Gloves are not normally required.
- Eye protection** : Safety glasses should be worn.
- Skin protection** : Protective equipment is not normally necessary.
- Hygiene measures** : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
- Environmental exposure controls** : Refer to section 6 and 12.
- Additional information** : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Appearance**

**Form:** Liquid                      **Colour:** Amber                      **Odour:** Aromatic odour

**Other data**

- Boiling point/range** :  $\geq 260$  °C
- Flash point** : 271 °C (Closed Cup)
- Explosive properties** : No
- Specific Gravity** : 0.842
- Viscosity** : 68 mm<sup>2</sup>/s at 25°C.
- Oxidizing properties** : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

- Stability** : Stable under normal usage conditions.
- Conditions to avoid** : None established.
- Materials to avoid** : Can react with strong oxidising agents.

**MOLYKOTE(R) L-1568 PROCESS GAS OIL**

**Hazardous decomposition products** : See section 11.

**11. TOXICOLOGICAL INFORMATION**

**On contact with eyes** : May cause temporary discomfort.

**On skin contact** : No adverse effects are normally expected.

**If inhaled** : No adverse effects are normally expected.

**On ingestion** : No adverse effects are normally expected.

**Other Health Hazard Information** : Product may emit formaldehyde vapours at temperatures above 150°C in the presence of air. Formaldehyde vapour is harmful by inhalation and irritating to eyes and respiratory system at breathing concentration less than one part per million (1 ppm).

<sup>1</sup> Based on product test data.

<sup>2</sup> Based on test data from similar products.

**12. ECOLOGICAL INFORMATION****Environmental fate and distribution**

The organic components contained in the product are biodegradable, however they are not classified as readily biodegradable. Organic solvents may evaporate into the atmosphere, where they degrade.

**Ecotoxicity effects**

No adverse effects on aquatic organisms are predicted.

**Bioaccumulation** : No specific information is available.

**Fate and effects in waste water treatment plants**

No adverse effects on bacteria are predicted.

**13. DISPOSAL CONSIDERATIONS**

**Product disposal** : Dispose of in accordance with local regulations.

**Packaging disposal** : Dispose of in accordance with local regulations.

**MOLYKOTE(R) L-1568 PROCESS GAS OIL****14. TRANSPORT INFORMATION****Road / Rail (ADR/RID)**

Not subject to ADR/RID.

**Sea transport (IMDG)**

Not subject to IMDG code.

**Air transport (IATA)**

Not subject to IATA regulations.

**15. REGULATORY INFORMATION****Labelling according to EEC Directive****S-phrases** : S51 Use only in well-ventilated areas.**National legislation / regulations****Ozone depleting chemicals** : No ozone depleting chemicals are present or used in manufacture.**Status****EINECS** : All ingredients listed or exempt.**TSCA** : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**MOLYKOTE(R) L-1568 PROCESS GAS OIL****16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.