

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Trade name : MOLYKOTE(R) P-1500

**Company** : Dow Corning Europe S.A.

rue Jules Bordet - Parc Industriel - Zone C

B-7180 Seneffe

Belgium

Service : Dow Corning (Wiesbaden) Tel: +49 611237507

Fax: +49 611237601

Dow Corning (Seneffe) Tel: +32 64511156

Fax: +32 64888683

Emergency Phone Number : Dow Corning (Barry U.K. 24h) Tel: +44 1446732350

Tel: +49 61122158 Tel: +32 64 888240

E-mail address (Safety Data

Sheet)

sdseu@dowcorning.com

Dow Corning (Wiesbaden 24h)

Dow Corning (Seneffe 24h)

**Use of the** : Lubricants and additives

substance/preparation

### 2. HAZARDS IDENTIFICATION

### The principal hazards of the product as supplied are:

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Inorganic and organic compounds in mineral oil

Hazardous Ingredients:					
Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Distillates (petroleum), solvent refined heavy naphthenic	64741-96-4	265-097-6	30.0		
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	Exempt or not available	27.0		
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	6.1		
N-Tallow Alkyltrimethylenediamine Oleate	61791-53-5	263-186-4	2.4	C N	R34 R50
Zinc oxide	1314-13-2	215-222-5	1.7	N	R50/53



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

4. FIRST AID MEASURES

**On contact with eyes** : Flush with water.

**On skin contact** : Flush with water.

**If inhaled** : Remove to fresh air.

On ingestion : No first aid should be needed.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : On large fires use dry chemical, foam or water spray (fog). On small fires use carbon

dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed

containers.

Unsuitable extinguishing

media

None known.

**Hazards during fire fighting** : None known.

Special protective

equipment/procedures

A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

keep fire exposed containers cool.

**Hazardous Combustion** 

**Products** 

Thermal breakdown of this product during fire or very high heat conditions may evolve

the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Phosphorus products. Nitrogen products. Traces of

fluorinated products.

6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** : Wear proper protective equipment.

**Environmental precautions**: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or

other appropriate barriers.

**Methods for cleaning up** : Scrape up and place in a container fitted with a lid. The spilled product produces an

extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling : Avoid skin and eye contact. Local ventilation is recommended. General ventilation is

recommended. Do not breathe spray or mist. Do not breathe fumes.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

**Advice on storage** : Do not store with oxidizing agents.

**Specific uses** : Refer to technical data sheet available on request.

Unsuitable packaging

materials

None known.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering Controls**: Ventilation: Refer to Section 7

#### **Exposure controls for hazardous components**

Name	CAS-No.	<b>Exposure Limits</b>
Distillates (petroleum), solvent refined heavy naphthenic	64741-96-4	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	10 mg/m3 STEL Oil Mist,mineral 5 mg/m3 TWA Oil Mist,mineral

#### Personal protection equipment

**Respiratory protection**: Suitable respiratory protection should be worn if the product is used in large quantities,

confined spaces or in other circumstances where the OEL may be approached or

exceeded.

A suitable respirator must be worn if the product is used in any circumstances where an

aerosol or mist may be generated, such as during spraying or similar activities.

Depending on the working conditions, wear a respiratory mask with filter(s) BP or use a

self-contained respirator.

The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection

supplier.

**Hand protection** : Chemical protective gloves should be worn: Silver shield(TM). 4H(TM). Viton(TM).

Regarding glove's breakthrough time, contact your chemical protective glove supplier.

**Eye protection** : Safety goggles should be worn.

**Skin protection**: Wear impervious overalls in circumstances where significant skin contact can occur.

**Hygiene measures** : Exercise good industrial hygiene practice. Wash after handling, especially before eating,

drinking or smoking.

**Environmental exposure** 

controls

Refer to section 6 and 12.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

Additional information

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Form: Paste Colour: White Odour: Very little

Important health, safety and environmental information

**Explosive properties** : No

Specific Gravity : 1.05

Oxidizing properties : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

#### 10. STABILITY AND REACTIVITY

**Stability** : Stable under normal usage conditions.

**Conditions to avoid** : None established.

**Materials to avoid** : Can react with strong oxidising agents.

**Hazardous decomposition** 

products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned

carbon compounds. Formaldehyde. Phosphorus products. Nitrogen products. Traces of

fluorinated products.

## 11. TOXICOLOGICAL INFORMATION

On contact with eyes : Slightly irritating.

On skin contact : Can irritate on prolonged or repeated contact. Repeated or prolonged contact may cause

defatting of the skin, leading to dermatitis.

**If inhaled** : No adverse effects are normally expected.

On ingestion : Small amounts transferred to the mouth by fingers during use should not injure.

Swallowing large amounts may cause digestive discomfort.

Other Health Hazard

**Information** 

: This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the

current physical form of the product, which is not in a respirable form.

Product may emit formaldehyde vapour at temperatures above 150°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to

eyes and the respiratory system. Exposure limits should be strictly respected.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

- Based on product test data.
- Based on test data from similar products.

### 12. ECOLOGICAL INFORMATION

### **Environmental fate and distribution**

Solid material, insoluble in water.

### **Ecotoxicity effects**

Very toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. However, due to the physical form and water-insolubility of the product the bioavailability is negligible.

### Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

#### 13. DISPOSAL CONSIDERATIONS

**Product disposal** : This material must be disposed of as hazardous waste. According to the European Waste

Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal

authorities.

Packaging disposal : Dispose of in accordance with local regulations. Waste codes should be assigned by the

user, preferably in discussion with the waste disposal authorities.

## 14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

UN No. : UN 3077

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.(Tallowalkyltriethylene diamineoleate / Zinc Oxide)

**Class** : 9

Packing group : III

Labels : 9

Sea transport (IMDG)

UN No. : UN 3077

**Proper Shipping Name** : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.(Tallowalkyltriethylene diamineoleate / Zinc Oxide)



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

Class : 9

Packing group : III

**Emergency Schedule** 

(EmS)

: F-A S-F

Marine pollutant : Tallowalkyltriethylene diamineoleate

Zinc Oxide

Labels : miscellaneous

Air transport (IATA)

UN No. : UN 3077

**Proper Shipping Name** : Environmentally hazardous substance, solid, n.o.s.(Tallowalkyltriethylene diamineoleate /

Zinc Oxide)

**Class** : 9

Packing group : III

Labels : Miscellaneous dangerous goods

: Apply Gross Wt Supplemental Label to Outer Package if shipping Limited Quantity

### 15. REGULATORY INFORMATION

### **Labelling according to EEC Directive**

**Symbols** : N Dangerous for the environment.

**R-phrases**: R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

**S-phrases** : S24/25 Avoid contact with skin and eyes.

S29 Do not empty into drains.

S51 Use only in well-ventilated areas.

S57 Use appropriate container to avoid environmental contamination. S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

### National legislation / regulations

Ozone depleting

chemicals

: No ozone depleting chemicals are present or used in manufacture.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0

Revision Date: 20.04.2010

# MOLYKOTE(R) P-1500

**Status** 

**EINECS** : All ingredients listed, exempt or notified (ELINCS).

TSCA : All chemical substances in this material are included on or exempted from listing on the

TSCA Inventory of Chemical Substances.

**IECSC** : All ingredients listed or exempt.

#### 16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

**R34** Causes burns., **R50** Very toxic to aquatic organisms., **R50/53** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.